

DART SCOOTER



Dart 3 Wheel



Dart 4 Wheel

OWNER'S MANUAL

driveTM




TABLE OF CONTENTS

1.	PREFACE AND INTRODUCTION	2
2.	SAFETY NOTICE.....	3
	2.1 Before driving	
	2.2 While driving	
	2.3 Labeling	
	2.4 EMI	
3.	PARTS INTRODUCTION.....	7
4.	OPERATION.....	8
	4.1 Control panel	
	4.2 How to operate your scooter	
	4.3 How to set to freewheel mode	
5.	DRIVING ON THE ROAD.....	13
6.	BATTERY CHARGING AND CARE.....	14
	6.1 Charging the battery	
	6.2 Battery	
	6.3 Replacing batteries	
7.	INSPECTION AND MAINTENANCE.....	18
	7.1 Inspection	
	7.2 Regular checking record	
	7.3 Battery, fuse and tire	
	7.4 Storage	
	7.5 Moving about	
	7.6 Assembling the scooter	
8.	TROUBLESHOOTING.....	21
9.	SPECIFICATION.....	22
10.	WARRANTY.....	23

1. PREFACE AND INTRODUCTION

Please carefully read this owner's manual before using the vehicle. Improper use of the vehicle could result in harm, injury or traffic accidents. To ensure that you get the most your scooter, please read this owner's manual before using.

- ◆ This owner's manual includes operation instructions for every aspect of the vehicle, assembly instructions, as well as instructions for how to deal with possible accidents.
- ◆ The symbols used in this manual are explained as follows:

 Warning	Improper usage could result in serious injury or death
 Attention	Improper usage could lead to injury and/or damage to your scooter.
 Suggestion	Follow these instructions to keep your vehicle in a good operating order.

- ◆ This manual includes a copy of repair and maintenance record chart and warranty information. Please keep it in a safe place or in the scooter.
- ◆ If someone else uses the scooter, please make sure that you provide him or her with this owner's handbook for his or her consideration.
- ◆ As designs change some illustrations and pictures in the manual may not correspond to the vehicle that you purchased. We reserve the right to make design modifications.

2. SAFETY NOTICE

2.1 BEFORE DRIVING

The user needs to be familiar with the usage and operation of this vehicle before driving. Therefore, please follow the commendations in this safety notice.

■ **The same traffic rules apply to the use of this vehicle as apply to pedestrians**

- ◆ For your safety, please follow and adhere to the same traffic laws as pedestrians.
- ◆ Please do not drive your scooter after consuming alcohol or when you are tired.
- ◆ Please be careful when driving your scooter in low light. It has not been designed for use at night.
- ◆ Be extremely cautious when driving your scooter in busy areas or in shopping malls.
- ◆ Ride on the paved roads or pedestrian areas only. Never ride on motorways or dual carriageways.
- ◆ Be aware of traffic when crossing or using roads.

■ **Practice operating your vehicle**

Before using the scooter in busy or potentially dangerous areas, familiarize yourself with the operation of your scooter. Please practice in a wide and open area like a park. In order to avoid accidents with your scooter whilst driving, please bear in mind driving motions, such as accelerating, stopping, turning, reversing, up-and down ramps.

- ◆ Turn the speed dial to minimum value for your initial practice.
- ◆ Be sure someone accompanies you for safety when driving on the roads for the first time.
- ◆ Only use higher speed setting when you are confident that you can easily operate and control your scooter.

■ **The Scooter is only to be used by one person at a time**

Do not carry passengers on your scooter (including children)

■ **Do not use this vehicle to carry or haul goods**

- ◆ The maximum weight that can be carried is 285lbs/130kg (including occupant and any goods). Refer to “MAX LOAD WEIGHT” in “9. SPECIFICATION”

■ **Please carry out daily inspections.**

Refer to the section entitled “DAILY CHECKING”

2. SAFETY NOTICE

2.2 WHILE DRIVING

■ Do not use your vehicle under the circumstances below.

- ◆ On surfaces that are muddy, gravelly, bumpy, narrow, snowed over, or icy,
- ◆ Do not drive at night or when it is raining, snowing, misty, or windy.
- ◆ Do not drive your vehicle in an “S” pattern or make erratic turnings.
- ◆ Do not take the scooter onto escalators.
- ◆ UNDER NO CIRCUMSTANCES SHOULD THE SCOOTER BE USED AS A SEAT IN A MOTOR VEHICLE (E.G. CARS, BUSES, TRAINS, ETC).

■ About Mobile Phones and other electrical equipment

- ◆ Do not use a mobile phone or other wireless communication devices while driving.
- ◆ Always switch off the scooter and remove the ignition key before using a mobile phone.
- ◆ Do not charge the mobile phone or any other electrical devices from your scooter’s battery.

■ Automatic Power Shut Down

In order to avoid accidental battery run down, your scooter is equipped with an automatic power shut down facility. If the scooter is switched on, after remaining undisturbed for a period of thirty minutes it will automatically turn off. If this situation occurs, simply switch your scooter off and back on and it will be ready to use.

■ Ramps, inclines and drops

- ◆ Do not drive onto steep ramps greater than the specified gradient. Refer to the section entitled “CLIMBING ANGLE” in “9. SPECIFICATION“
- ◆ Always use a low speed setting when ascending or descending a gradient.
- ◆ Do not drive on roads with large drops or potholes. Refer to the section entitled “MAX. GROUND CLEARANCE” in “9. SPECIFICATION”.
- ◆ Please slow down when driving on roads with inclines.
- ◆ Do not make sudden turns when driving on gravel roads or ramps.
- ◆ Always lean forward when climbing a steep gradient.

2.3 LABELING

Carefully read all the labeling on the scooter before drive it.

2. SAFETY NOTICE

2.4 EMI

This portion of the content will provide the user with basic information that describes the problems with EMI, known sources of EMI, protective measures either to lessen the possibility or exposure or to minimize the degree of exposure, and suggested action should unexpected or erratic movement occur.

Caution: It is very important that you read this information regarding the possible effects of electromagnetic interference on your electric SCOOTER.

■ ELECTROMAGNETIC INTERFERENCE (EMI) FROM RADIO WAVE SOURCES

Powered vehicle may be susceptible to electromagnetic interference (EMI), which is interfering electromagnetic energy (EM) emitted from sources such as radio stations, TV stations, amateur radio (HAM) transmitters, two-way radios, and mobile phones. The interference (from radio wave sources) can cause the powered scooter to release its brakes, move by itself, or move in unintended directions. It can also permanently damage the powered scooter's control system. The intensity of the interfering EM energy can be measured in volts per meter (V/m). Each powered scooter can resist EMI up to a certain intensity. This is called its "immunity level". The higher the immunity level, the greater the protection. At this time, current technology is capable of achieving at least a 20 V/m immunity level, which would provide useful protection from the more common sources of radiated EMI. This powered scooter model as shipped, with no further modification, has an immunity level of 20 V/m without any accessories.

There are a number of sources of relatively intense electromagnetic fields in the everyday environment. Some of these sources are obvious and easy to avoid. Others are not apparent and exposure is unavoidable. However, we believe that by following the warning listed below, your risk to EMI will be minimized.

The sources of radiated EMI can be broadly classified into three types:

1. Hand-held portable transceivers (transmitter-receivers with the antenna mounted directly on the transmitting unit. Examples include: citizens band (CB) radios, "walkie talkie", security, fire, and police transceivers, cellular telephones and other personal communication devices.

Note: Some mobile telephones and similar transmit signal while they are ON, even when not being used;

2. Medium-range mobile transceivers, such as those used in police cars, fire trucks, ambulances and taxis. These usually have the antenna mounted on the outside of the scooter.

2. SAFETY NOTICE

3. Long-range transmitters and transceivers, such as commercial broadcast transmitter (radio and TV broadcast antenna towers) and amateur (HAM) radios.

Note: Other types of hand-held devices, such as cordless phones, laptop computers, AM/FM radios, TV sets, CD player, and cassette players, and small appliances, such as electric shavers and hair dryers, so far as we know, are not likely to cause EMI problems to your powered scooter.

■ **POWERED VEHICLE ELECTROMAGNETIC INTERFERENCE (EMI)**

Because EM energy rapidly becomes more intense as one moves closer to the transmitting antenna (source), the EM fields from hand-held radio wave sources (transceivers) are of special concern. It is possible to unintentionally bring high levels of EM energy very close to the control system of powerchair while using these devices. This can affect powered vehicle movement and braking. Therefore, the warnings listed below are recommended to prevent possible interference with the control system of the powered scooter.

■ **WARNINGS**

Electromagnetic interference (EMI) from sources such as radio and TV stations, amateur radio (HAM) transmitters, two-way radios, and mobile phones can affect powered scooter and motorized scooter. Following the warnings listed below should reduce the chance of unintended brake release or powered scooter movement which could result in serious injury.

1. Do not operate hand-held transceivers-receivers), such as citizens band (CB) radios, or turn ON personal communication devices, such as cellular phones, while the powered vehicle is turned ON;
2. Be aware of nearby transmitters, such as radio or TV stations, and try to avoid coming close to them;
3. If unintended movement or brake release occurs, turn the powered vehicle OFF as soon as it is safe;
4. Be aware that adding accessories or components, or modifying the powered vehicle, may make it more susceptible to EMI (Note: There is no easy way to evaluate their effect on the overall immunity of the powered scooter).
5. Report all incidents of unintended movement or brake release to the powered scooter manufacturer, and note whether there is a source of EMI nearby,

■ **IMPORTANT INFORMATION**

1. 20 Volts per meter (V/m) is a generally achievable and useful immunity level against EMI (the higher the level, the greater the protection);
2. This product has an immunity level of 20 V/m without any accessories and connected to it.

3. PARTS INTRODUCTION

PARTS DESCRIPTION

- 1. Control panel
- 2. Tiller Adjustment Knob
- 3. Seat
- 4. Battery Pack
- 5. Freewheel Lever
- 6. Anti-tip wheels
- 7. Seat Post Knob



4. OPERATION

4.1 CONTROL PANEL

1. Speed Dial
2. Battery Indicator




4.2 HOW TO OPERATE YOUR SCOOTER

■ Power switch

- ◆ To switch the power on , turn the key clockwise in the ignition. The power eye should illuminate.
- ◆ To switch the power off , turn the key counter clockwise . The power eye should switch off and the key can be removed if required.

■ Speed Dial

Turn the speed dial to determine the maximum speed of the scooter. Turn the dial clockwise to increase the speed setting and turn the dial counter clockwise to decrease the speed setting.



Slowest setting

Fastest setting

■ Moving and Braking

- ◆ Push the right-hand side speed control lever forward with your right thumb and the scooter will move forward.
- ◆ Push the left-hand side speed control lever forward with your left thumb and the scooter will move backward.
- ◆ To brake , release the speed control lever which will return to neutral and activate the electromagnetic brake automatically .This will bring the scooter to a prompt stop.
- ◆ The speed control lever allows you to control the speed of the scooter up to a maximum speed determined by the Speed Dial .The further the speed control lever is deflected, the faster the scooter will go.

■ Braking

Electro-magnetic brake: Release the speed control lever completely, and the electromagnetic brake will be activated automatically, and the scooter will stop.

4. OPERATION


⚠ Warning

When on a gradient NEVER set the vehicle to the freewheel mode. The electromagnetic brakes will not be applied. This may result in injury or damage.

■ Battery indicator

The battery indicator on the tiller console uses a color code to indicate the approximate power remaining in your batteries. Green indicates(40~100%) capacity, yellow a draining charge(10~30%),and red indicates that an immediate recharge is necessary.

- ◆ The remaining power suggested by the battery indicator will vary by the actual driving time incurred and how you drive. Repeated starting, stopping, climbing will consume the power more quickly.



■ Main Circuit Breaker (Reset Button)

When the voltage in your scooter's batteries becomes low or the scooter is heavily strained because of excessive loads or steep inclines, the main circuit breaker may trip to protect the motor and electronics from damage.

- ◆ The main circuit breaker reset button pops out when the breaker trips.
- ◆ When the breaker trips, the entire electrical system of your scooter shuts down.
- ◆ Allow a minute or two for your scooter's electronics to "rest".
- ◆ Push in the reset button to reset the main circuit breaker.



4. OPERATION


Suggestion

1. You should recharge the batteries after each time the vehicle is used to ensure maximum range. The batteries should be charged up at least once a week even if the scooter is not used.
2. After charging or replacing a new battery, drive the vehicle for 2-3 minutes to make sure the battery capacity is sufficient.
3. In cold weather, the battery may respond more slowly and the battery range may be reduced.
4. When driving on a gradient, the battery indicator light might move up and down. This is a normal phenomenon.
5. Even if the battery is used properly, it is natural for the battery's capacity to reduce with time, which results in reduced battery range. If after a full charge you find the battery's range is about only 50% of the range when the batteries were new, it is necessary to replace the batteries. Please see your dealer about replacement batteries. If you continue to use the old battery when it should be replaced, it could lead to a rapid decline in performance.
6. The battery range will be reduced when driving frequently on a slope or rough terrain, as this leads to greater consumption of power.
7. The batteries have a six-month warranty covering manufacturing defects. This warranty does not cover faults due to incorrect battery recharging.

■ How to adjust the seat height

1. Remove the seat from your scooter.
2. Remove the lock bolt from the lower seat post.
3. Adjust the seat post to the desired seat height.
4. Move the upper seat post so that there is a hole to insert the lock bolt.

4.3 HOW TO SET TO FREEWHEEL MODE



4. OPERATION

- ◆ Engaged mode : Push the lever completely and the scooter can be driven by motor power.
- ◆ Freewheel Mode. GPull the lever up and the scooter can be moved manually.

Warning

Never operate the freewheel lever while seated on the scooter or on an incline!

OPERATION OF THE FREEWHEEL LEVER

- Always pull UP FIRMLY for freewheel mode
- Always push DOWN FIRMLY for drive mode

■ Tiller Adjustment

The tiller can be adjusted in to many different positions to suit each driver.

1. Loosen the lever to adjust the tiller to positions you want. (Fig. 4.3)
2. Once the proper position is determined, tighten the lever to secure the tiller.(Fig.4.4)



Fig. 4.3 Fig. 4.4

Warning

- ◆ Hold the tiller before loosening the tiller adjustment knob.
- ◆ Before lifting or driving the scooter make certain the tiller adjustment knob is fully tightened.
- ◆ Never attempt to adjust the tiller while the scooter is motion.

4. OPERATION

■ DISASSEMBLING THE SCOOTER

1. Raise from the tiller to keep the scooter stand in an upright position. (Fig. 4.5)
2. To pull out the frame connection pin, push the front frame. (Fig. 4.6)
3. Incline the front frame to 45 degree. (Fig. 4.7)
4. Pull to separate the front frame from the rear frame. (Fig. 4.8)



Fig. 4.5



Fig. 4.6



Fig. 4.7



Fig. 4.8

Suggestion

The assembly process is essentially the disassembly process in reverse. First study the text and photographs in the disassembly procedure before re-assembling the scooter.

5. DRIVING ON THE ROAD

■ Starting and Driving

1. Make sure the seat is installed properly.
2. Make sure the tiller has been secured properly.
3. Turn the power switch to “ON”.
4. Check battery indicator to see whether there is enough power for operation. If you have doubt about the remaining power, please recharge the batteries.
5. Set the speed dial to a position you feel safe and comfortable with.
6. Check the forward/reverse speed lever works correctly.
7. Make sure the electromagnetic brake works correctly.
8. Before driving, ensure it is safe to do in the environment around you.

☞ Attention

1. Do not push both RH & LH sides of the speed control lever simultaneously. This might leave you unable to control your scooter.
2. Do not turn the power switch to OFF while driving as this will lead to an emergency stop and possible risk of accident and injury.
3. Do not set to the highest speeds whilst driving indoors.
4. Do not adjust the speed dial whilst driving, a sudden change in speed may cause danger to you and others, and may cause damage to your scooter.
5. Do not place magnetic devices near the area of the operation handle as this could affect the safe operation of your scooter. The scooter controller is located under the foot way.
6. Do be careful whilst driving in heavy traffic or crowded areas.
7. While reversing the vehicle, beware of people or objects behind you.

◆ Stopping

1. Release the speed control lever completely. The vehicle will naturally brake and stop.
2. Turn the power off. Then pull out the key.

☞ Attention

1. The stopping distance will vary with your forward / reverse speed. Begin braking as early as you can.
2. When parking your scooter, be sure to park on flat ground and then turn the power to “OFF” before you dismount.

6. BATTERY CHARGING AND CARE

6.1 CHARGING THE BATTERY

■ Off-board Charging (see photograph below)

1. Turn the power switch to (OFF)
2. Remove the battery pack by opening the battery compartment and lifting out the battery pack by the handle.
3. Plug the charger's power cord into an outlet.
4. Plug the charger's round plug into the charging socket of the battery pack.
5. Both the charger's red and orange LED will be lit when beginning charging. The charging duration is about 6 hours. To ensure optimum performance a 10-hour charge is recommended.
6. Both the charger's LED will be lit during the charging process. The orange LED will turn green when charging is complete.
7. Turn off the charger, disconnect the power cord and the round plug from charger socket on the battery pack.



6. BATTERY CHARGING AND CARE

■ Charging Hours

The charging duration is about 6 hours. To ensure optimum performance a 10-hour charge is recommended. But we do not recommend a charging more than 24 consecutive hours.

■ Batteries (Inside the Pack)

1. The Dart is powered by two sealed lead-acid deep-cycle batteries.
2. The batteries supplied with the scooter are 12 V 12AH batteries.

⚠ Warning

1. Keep away from flammable objects while charging as it may lead to fire or explosion of battery.
2. Do not smoke while charging as the battery may release hydrogen gas. Always charge your battery in a well-ventilated space.
3. Never connect or disconnect the plug or cord with wet hands while charging. Do not connect or disconnect the plug or cord when they are wet, it may lead to electric shock.

⚠ Attention - Please follow the rules below to avoid accidents while charging.

1. Please use the Drive charger only, and recharge the battery to its full capacity every time. You may damage the battery and scooter if you use a charger, which is not to the correct specification.
2. Please charge in a well-ventilated space where it is not directly exposed to the sunlight. Do not charge in surroundings where it is humid or under rainfall and morning dews.
3. Do not charge in temperatures less than 14°F (-10°C) or higher than 120°F (+50°C) as the charger may not work well and the batteries may become damaged.

6.2 BATTERY

- ◆ Do not expose the battery to temperatures below 50°F (10°C) or above 120°F (50°C) when charging or storing the vehicle. Under the above temperature range can cause the battery either to freeze or over heat. This will damage the batteries and shorten their life.
- ◆ These batteries are maintenance free and there is no need to fill with water.
- ◆ You should charge the batteries at least once a week.

6. BATTERY CHARGING AND CARE

- ◆ The batteries carry a six-month manufacturer's warranty. This warranty only covers issues relating to manufacturing faults, and not faults relating to failure to recharge the batteries as instructed above.

Suggestion– How to maximize your batteries efficiency and service life

1. Fully recharge your new battery before its first time use.
2. Be sure to fully charge the battery fully every time. The battery life will be shortened or decayed if the battery is repeatedly used without being fully charged.
3. Always complete the charging until the orange LED light turns green. NEVER stop charging before it is complete.
4. Keep your batteries fully charged whenever possible.
5. If you do not use your scooter for a long time, it should be charged at least every week to keep the battery in a fully usable condition.
6. The ambient temperature will affect charging time. Charging time will be longer in cold weather.
7. After charging, do not leave the charger socket plugged in to the scooter, as this will cause a power drain on the scooter and temporarily reduce its range.

■ **Cleaning the battery**

If the batteries are contaminated by water, battery acid, dust or other substances, they will discharge quickly. The batteries supplied with the scooter are sealed and as such are maintenance free with no risk of battery leakage. Please follow the steps below to clean the battery.

1. Turn the scooter power switch to OFF.
2. Follow the procedure in the next section “Replacing the Batteries”.
3. Use a clean cloth to wipe off the soiled area.
4. Take out the battery.
5. Clean the battery with a clean cloth. If the terminal is covered by white powder, please wipe it clean using warm water.

6.3 REPLACING BATTERIES

■ **Batteries replacement**

Follow the procedure below to replace the batteries:

1. Turn the battery pack remove switch to unlock
2. Remove the battery pack from the scooter.
3. Open the battery pack then disconnect the cables from the four battery terminals.
4. Remove the batteries from the battery pack.
5. Place new batteries inside the pack.

6. BATTERY CHARGING AND CARE

6. Connect the red cable to the positive (+) battery terminal and black cable to the negative (-) on the other battery.
7. Connect up the fused cable between the two batteries and close the battery pack.



⚠ Warning

1. The wiring system and charger are placed in the battery pack while being assembled in plant. Do not attempt to re-locate the wiring system by yourself. The improper layout of wiring system may result in the wires pinched by battery box, which might result in the electronic system failure.
2. Be sure the battery wires are connected to their right battery terminal.

📖 Suggestions

If necessary, ask for help from your dealer for advice about maintaining and replacing the battery.

📖 Suggestions

1. Make sure the terminals are installed properly and put the cover back on.
2. Do not use the battery to charge telecom equipment or other items.
3. Battery efficiency will vary with outside conditions; the driving distances will be shorter in cold weather. If the vehicle is not used for a long time, charge the battery at least every week.
4. Replace both batteries together.

7. INSPECTION AND MAINTENANCE

7.1 INSPECTION

- Clean the scooter with a damp cloth and dust down approximately once a week to preserve the appearance of the scooter.
- Adjust the tiller height and return to the original position and swivel the seat once a week to ensure the parts adjust and remove smoothly and easily when required.
- Check for signs of wear and tear on the tires and the upholstery on a regular basis.
- For optimum performance and to increase the lifespan of your scooter, it is recommended that you have your scooter serviced once a year.

7.2 REGULAR CHECKING RECORD

Make sure your scooter is correctly serviced. Take it to your dealer for regular maintenance checks. This should be at six months intervals after an initial inspection after one month. Your dealer may charge a fee for this. The checking record is shown below.

YEAR	1	2	3	4	YEAR	1	2	3	4
Service Dates					Service Dates				
Controller					Upholstery				
On/off switch					Seat				
Control Lever					Back				
Braking					Armrests				
Recharge point					Electrics				
Batteries					Connections condition				
Levels					Harness				
Connections					Test run				
Discharge test					Forwards				
Wheels and Tires					Reverse				
Wear					Emergency stop				
Pressure					Left turn				
Bearings					Right turn				
Wheel nuts					Slope test				
Motors					Over obstacles				
Wiring					List Items repaired				
Noise									
Connections									
Brake									
Brushes									
Chassis									
Condition									
Steering									

7. INSPECTION AND MAINTENANCE

7.3 BATTERY, FUSE AND TIRE

■ Battery

Refer to the section entitled “6. BATTERY CHARGING AND CARE ”.

■ Fuse

If the battery charger is turned on and no LED are lit, check the fuse.

Suggestion

Ask for help from your dealer to inspect or replace the fuse, since the tiller shroud has to be removed first before you can replace the fuse.

■ Tires

The condition of the tires depends on how you drive and use your scooter.

- ◆ Check the tread depth regular.
- ◆ Replace the tires when the tread depth is less than 0.5mm.

7.4 STORAGE

Make sure the scooter is stored under the following circumstances:

- Ensure the scooter is switched off
- Ensure the charger is disconnected when not in use

Suggestion

Please store the scooter in a location where it is out of direct sunlight, rain, or moisture. When storing for a long time, please charge the battery to full power and then disconnect the battery terminal. For details inquire to your dealer.

7. INSPECTION AND MAINTENANCE

7.5 MOVING ABOUT

- ◆ Switch off the power with power key before moving.
Always dismount from the scooter before moving.
- ◆ Lift the scooter by the chassis, and not by the shroud.
Lifting the scooter by the bumper could cause damage or injury.
- ◆ For your safety, always ask for help if required. You will need two people when moving or lifting the scooter.
If you are on your own, disassemble the scooter before lifting. Refer to the section below.

Warning

Always unplug the rear section electrical connector before separating the two sections.

7.6 ASSEMBLING THE SCOOTER

Suggestion

The assembly process is essentially the disassembly process in reverse. First study the text and photographs in the disassembly procedure before re-assembling the scooter.

1. Loosen tiller adjustment knob, raise the tiller to the desired position, and then tighten the tiller adjustment knob.
2. Reinstall the upper seat post at the desired height. Secure with the locking pin and tighten the seat post knob.
3. Reinstall the batteries by lowering it in to place.
4. Replace the seat and rotate it until it locks into its correct position.

Warning

After assembling the Dart make absolutely certain the tiller adjustment knob is fully tightened.

8. TROUBLESHOOTING

■ TROUBLE SHOOTING

If you have trouble with your scooter, you can inspect the following before taking your scooter to the dealer.

If you cannot solve the problem, contact your dealer for assistance.

Problem	Symptom	Remedy
The scooter will not switch on	<ul style="list-style-type: none"> • Batteries not connected. • Rear and front sections not connected • Circuit breaker has tripped 	<ul style="list-style-type: none"> • Check batteries are connected • Check connection on front – to - rear loom • Push circuit breaker button to rest
The scooter switch on but will not run	<ul style="list-style-type: none"> • Flat batteries • Charger plugged in • Motor in freewheel mode 	<ul style="list-style-type: none"> • Check battery power • Unplug charger • Re-engage the freewheel lever
Scooter appears slow	<ul style="list-style-type: none"> • Flat batteries • Speed setting slow 	<ul style="list-style-type: none"> • Check battery power and /or recharge • Check the speed dial is not set at low
The seat moves whilst in use	<ul style="list-style-type: none"> • Seat not locked in position 	<ul style="list-style-type: none"> • Slowly rotate the seat until it drops in to place and is secure
The tiller appears loose	<ul style="list-style-type: none"> • Tiller adjustment knob loose 	<ul style="list-style-type: none"> • Tighten the tiller adjustment knob
Involuntary horn sounds	<ul style="list-style-type: none"> • There is fault on the scooter 	<ul style="list-style-type: none"> • Ensure the control lever is released and switch the scooter on and off recharge batteries

9. SPECIFICATION

SPECIFICATIONS

Model	Dart 3 Wheel	Dart 4 Wheel
Dimension (LxWxH inch) (LxWxH mm)	38" x 19" x 38.5" 970mm x 480mm x 920 mm	37"x19"x35.5" 940mm x 490mm x 900mm
Base weight (without battery)	55lbs /25kg	57lbs /26kg
Battery weight	22lbs /10kg	
Seat weight	16.5lbs / 7.5kg	
Total weight	88lbs / 41.5kg	95lbs / 43.5kg
Battery	12 Ah/12V x 2	
Charger	1.5A Off-Board	
Charging time, hours	>8h	
Front Wheel	8"x2"/200mmx50mm	
Rear Wheel	8"x2"/200mmx50mm	
Anti-tip Wheel	2"/50mm	
Driving System	Direct rear wheels (with differential gear)	
Brake System	Electromagnetic brake	
Control Method	By speed control lever	
Top Speed	4 mph / 6.4kph	
Turning radius	32.2"/818mm	35.4"/900mm
Climbing angle	6°	
Cruising range	Up to 7.5miles / Up to 12km	
Max. User weight	285lbs / 130kg	

Remark: The manufacturer reserves the right to modify the specification if necessary. The final specification is subject to the individual scooter you purchase from your dealer.

Note:

Range may vary due to climate, user's weight, terrain, and battery charge condition.

10. WARRANTY

9.1 WARRANTY

There is a limited lifetime warranty on your new Dart Scooter. The warranty covers the scooter for parts only during this period. For more detail, please see the Warranty Conditions below.

Warranty Conditions:

Any work or replacement part installation must be carried out by an authorized Drive dealer / service agent. To apply the warranty should your scooter require attention please contact your service provider.

The warranty on your new Dart scooter is as follows:

- a) Frame: Limited Lifetime Warranty
- b) Electronics: 14 months limited warranty
- c) Battery: 6 months

Note: The warranty is not transferable

Any replaced parts will be covered by this warranty for the balance of the warranty period on the scooter.

Parts replaced after the original warranty has expired will be covered by a three months warranty.

Wearable items will not generally be covered under the normal warranty period, which includes but not limited to the seat assembly or cover, tires, shroud, armrests, footplates, and lights.

The above warranty conditions apply to brand new scooters purchased at the full retail price. If you are unsure whether your scooter is covered, check with the service agent.

Under normal circumstances, no responsibility will be accepted where the scooter has failed as a direct result of:

- a) The scooter part not having been maintained in accordance with the manufacturer's recommendations.
- b) Failure to use the manufacturer's specified parts
- c) The scooter or part having been damaged due to neglect, accident or improper use
- d) The scooter or part having been altered from the manufacturer's specifications or repairs having been attempted before the service agent is notified

Please note your local service agent's contact details in the box below. In the event of your scooter requiring attention, contact them and give all relevant details so they can act quickly. The manufacturer reserves the right to alter without notices any weights, measurements or other technical data shown in this manual. All figures, measurements and capacities shown in this manual are approximate and do not constitute specifications.

DRIVE authorized Service Agent

Name
Address
Tel
Postcode



Drive Medical Design & Manufacturing

99 Seaview Boulevard
Port Washington, NY 11050
Phone: 516-998-4600
Fax: 516-998-4601
www.drivemedical.com